

Window Styles and Sizes						Frame Options				Glazing		Grid Options			Colors		Test Methods and Certifications									
Window Style	Product Series #	Configuration	Frame Depth	Minimum Size <small>Sizing based on actual frame size (DLO)</small>	Maximum Size <small>Sizing based on actual frame size (DLO)</small>	1/2" Flange	1-1/4" Nail Fin	Flange with Nail Fin	Box/Equal Leg	1/2" Flange Extension	Glazing Orientation	Laminated	Laminated Insulating	Double Raised Ogee	Traditional Simulated Divided Lite (SDL)	Flat Grid Between the Glass (CIG/GBG)	White	Bronze Exterior	AAMA A440 & ASTM E1886/1996		TAS 201, 202 & 203					
																			Design Pressure	Keystone Certification	Design Pressure	Miami Dade Notice of Acceptance	Independent 3rd Party Evaluation & Certification	Florida Building Code Product Approval	ENERGY STAR <sup>®</sup> *** <small>Meets 2010 Criteria</small>	
Double Hung	DH2760	X/X	3 1/4"	18 1/8" x 36 1/2" or 23" x 24"	53 1/4" x 78"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+65/-80	■	+65/-80 +65/-120*	Pending	■	■	■
	DH2860	X/X	3 1/4"	18 1/8" x 36 1/2" or 23" x 24"	53 1/4" x 78"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+65/-80	■	+65/-80 +65/-120*	Pending	■	■	■
Horizontal Roller	HR2710	XX	3 1/4"	24" x 23"	74 1/4" x 63 1/4"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+60/-65	■	+60/-65	Pending	■	■	■
	HR2710	XOX-1/3	3 1/4"	33 3/4" x 22 1/2"	109" X 63"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+60/-65 or +65/-80	■	+60/-65 or +65/-80	Pending	■	■	■
	HR2710	XOX-1/4	3 1/4"	45 1/4" x 22 1/8"	130" x 63"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+65/-65	■	+65/-65	Pending	■	■	■
	HR2810	XX	3 1/4"	24" x 23"	74 1/4" x 63 1/4"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+70/-100	■	+70/-100	Pending	■	■	■
	HR2810	XX	3 1/4"	24" x 23"	74 1/4" x 76"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+70/-100	■	+70/-100 +80/-140*	Pending	■	■	■
	HR2810	XOX-1/3	3 1/4"	33 3/4" x 22 1/2"	109" X 63"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+60/-80	■	+60/-80	Pending	■	■	■
	HR2810	XOX-1/3	3 1/4"	33 3/4" x 22 1/2"	109" X 63"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+75/-100	■	+75/-100	Pending	■	■	■
HR2810	XOX-1/4	3 1/4"	45 1/4" x 22 1/8"	130" x 63"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+75/-100	■	+75/-100	Pending	■	■	■	
HR2810	XOX-1/4	3 1/4"	45 1/4" x 22 1/8"	130" x 63"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	■	+75/-100	■	+75/-100	Pending	■	■	■	

SEE REVERSE SIDE FOR FIXED LITE/ARCHITECTURAL, CASEMENT AND AWNING

\* Maximum design pressure using comparative analysis on smaller sizes

\*\* Refer to PremierVue catalog for architectural shape size details

\*\*\* Refer to the PGT Energy Performance guide for details on product energy ratings and tax credit eligible options  
Miami Dade Notice of Acceptance application pending (approval expected Q2 2010)

Window Styles and Sizes						Frame Options				Glazing		Grid Options			Colors		Test Methods and Certifications								
Window Style	Product Series #	Configuration	Frame Depth	Minimum Size <small>Sizing based on actual frame size (DLO)</small>	Maximum Size <small>Sizing based on actual frame size (DLO)</small>	1/2" Flange	1-1/4" Nail Fin	Flange with Nail Fin	Box/Equal Leg	1/2" Flange Extension	Glazing Orientation	Laminated	Laminated Insulating	Double Raised Ogee	Traditional Simulated Divided Lite (SDL)	Flat Grid Between the Glass (CIG/GBG)	White	Bronze Exterior	AAMA A440 & ASTM E1886/1996		TAS 201, 202 & 203			Florida Building Code Product Approval	ENERGY STAR® *** <small>Meets 2010 Criteria</small>
																			Design Pressure	Keystone Certification	Design Pressure	Miami Dade Notice of Acceptance	Independent 3rd Party Evaluation & Certification		
Fixed Lite / Architecturals	PW2720 AR2720**	○	3 1/4"	14" x 14"	48 1/4" x 96" or 53 1/4" x 84 1/4"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+65/-80	■	+65/-80	Pending	■	■	
	PW2820 AR2820**	○	3 1/4"	14" x 14"	48 1/4" x 96" or 53 1/4" x 84 1/4"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+65/-80	■	+65/-80	Pending	■	■	
	PW2820 AR2820**	○	3 1/4"	14" x 14"	53" x 78"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+75/-120	■	+100/-120	Pending	■	■	
Casement	CA2740	X	3 1/4"	16 1/2" x 18"	36" x 76"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+65/-80	■	+65/-80	Pending	■	■	
	CA2840	X	3 1/4"	16 1/2" x 18"	36" x 76"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+65/-80	■	+65/-80	Pending	■	■	
	CA2840	X	3 1/4"	16 1/2" x 18"	36" x 76"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+80/-115	■	+80/-115	Pending	■	■	
Awning	AW2740	X	3 1/4"	18" x 16 1/2"	53 1/8" x 32"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+65/-80	■	+65/-80	Pending	■	■	
	AW2840	X	3 1/4"	18" x 16 1/2"	53 1/8" x 32"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+65/-80	■	+65/-80	Pending	■	■	
	AW2840	X	3 1/4"	18" x 16 1/2"	53 1/8" x 32"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+75/-100	■	+75/-100	Pending	■	■	
	AW2840	X	3 1/4"	18" x 16 1/2"	53 1/8" x 32"	■	■	■	■	■	Interior	■	■	■	■	■	■	■	+75/-100	■	+75/-100	Pending	■	■	

SEE REVERSE SIDE FOR DOUBLE HUNG AND HORIZONTAL ROLLER

\* Maximum design pressure using comparative analysis on smaller sizes  
 \*\* Refer to PremierVue catalog for architectural shape size details  
 \*\*\* Refer to the PGT Energy Performance guide for details on product energy ratings and tax credit eligible options  
 Miami Dade Notice of Acceptance application pending (approval expected Q2 2010)